

25M No Voltage Drop Strip

2835



Available colors

W NW WW SWW



RoHS



Features

- 2835 assembled LEDs.
- Built-in IC, constant current design. Standard constant voltage driver.
- Maximum connection length is 25m.
- The LED strip can be cut to meet requirements of different length.
- CE, RoHS, 5 years warranty.
- Different IP grades can meet the requirements in different environments.
- No resistor, fancy appearance.

Application

- Stage lighting;
- Festival, activities, exhibition lighting, etc;
- Backlight of signage;
- Contour lighting;
- LED luminous characters;
- Landscape decoration lighting.

Technical parameters

Model	Color	Lumen (lm/m)	LED CCT Range	LED Type	LED Qty. (leds /m)	Beam angle (degree)	DC Voltage (V)	Rated Watt (w/m)	IP	CRI
SC-2835CC-XX	W NW WW SWW	390 380 370 360	W(6000-6500K) NW(3800-4200K) WW(2900-3100K) SWW(2300-2500K)	2835	60	120	24	3.6	20/65/68	80

SC-2835CC-XX	SC-2835CCP-XX	IP65	PU glue potted	
	SC-2835CCS-XX	IP65	Silicon sleeved	
	SC-SF-2835CC-XX	IP68	Silicon extrusion and glued	

Dimensions

SC-2835CC-XX-24V

