


LED PIPE High OUTPUT
LED PIPE L900 HIGH OUTPUT WW
0051373



Product features

- LED T5 replacement batten, high output range: more lumens per meter with efficiency up to 125 lum/watt, seamless linking (up to 10M), ideal for direct lighting such as under cabinet or in kitchens, 120 degree beam angle, includes switch, includes 0.30m stripped cable, white polycarbonate body, includes standard and tilting brackets



NOTES

undefined

PRODUCT OVERVIEW

Product name	LED PIPE L900 HIGH OUTPUT WW
Technology	LED
Housing	PC Polycarbonate
General application	Residential & Consumer, Retail
ETIM Class	EC000109
E-number FI	4278218
Warranty	3 years
Fixture luminous flux (lm)	1325
Luminaire efficacy (lm/W)	115
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	11.5
Electrical protection	Class II
Dimmable	No
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288513737

DATA TABLE

General data	
Product name	LED PIPE L900 HIGH OUTPUT WW
Technology	LED
Housing	PC Polycarbonate

LED PIPE High OUTPUT

LED PIPE L900 HIGH OUTPUT WW

0051373

General application	Residential & Consumer, Retail
Operating temperature range (°C)	-20°C - 40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000109
E-number FI	4278218
Warranty	3 years

Optical data

Fixture luminous flux (lm)	1325
Luminaire efficacy (lm/W)	115
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Beam Angle (°)	120
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	11.5
Mains voltage (V)	220-240V~
Lamp power factor	0.7
Electrical protection	Class II
Dimmable	No
Drive current (mA)	100
Inrush Current (A)	100
Inrush Duration (µs)	150
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	111
Max. Luminaires per 13A C Breaker	144
Max. Luminaires per 16A C Breaker	181
Max. Luminaires per 20A C Breaker	222
Max. Luminaires per 10A B Breaker	65
Max. Luminaires per 13A B Breaker	86
Max. Luminaires per 16A B Breaker	107
Max. Luminaires per 20A B Breaker	133

Lifetime data

Lifespan L70 B50	30000
------------------	-------

Physical data

Housing colour	White
IP rating	IP20
IK rating	IK03
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	900
Nominal Product Width (mm)	24
Nominal Product Height (mm)	35
Weight (kg)	0.13

LED PIPE High OUTPUT

LED PIPE L900 HIGH OUTPUT WW
0051373


Packaging

Single packaging type	Carton
Product EAN number	5410288513737
Packaging single length / height (cm)	90.4
Packaging single width (cm)	4.6
Packaging single depth (cm)	3.1
DUN14 (outer)	15410288513734
Units per outer package	30
Packaging outer length / height (cm)	92.0
Packaging outer width (cm)	25.5
Packaging outer depth (cm)	22.0

Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS

